







Embedded Vision Camera Platform

iVS-CV22



Unlock the full potential of vision data for your application.

Embedded, modular, cloud-connected, and secure – iENSO develops and delivers vision systems for any application.

Key features:

- Quad-core Arm °Cortex°-A53 up to 1 GHz
- Up to 4Kp60 maximum encoding performance
- CNN / DNN inference acceleration for detection, classification, and more
- +700 MPixel/s input rate
- · Multi exposure HDR

- 180° and 360° fisheye lens distortion correction
- Single or dual sensor input with independent ISP configuration
- H.265/HVEC, H.264, MJPEG encoding
- Support for 32-bit LPDDR4 / LPDDR4x
- Secure boot with TrustZone® and secure memory
- Based on 10nm low-power CMOS process

Sensor 1 Connector		Wi-Fi Module		
Sensor 2 Connector	Image Signal Processor (ISP)	Quad-Core ARM® CORTEX A53 NEON DSP Extension	Computer Vision Processor CVFlow™	POE Module
ALS/IRC Connector	System Peripherals Timers, UART, JTAG, SPI, RTC, I2C, I2S, GPIO, PWM, ADC	Memory LPDDR4, 32-Bit SPI NAND	Video CODEC AVC/HVEC/MJPEG Multi-CH, Encode	Connector LTE Module Connector
PIR/Motion Connector MIC Connector	Interfaces/Inputs MIPI CSI-2, PIR, ALS, Mic	Security Features Secure Boot – Trust Zone®, TRNG, OTP, DRAM Scrambling and DRAM Virtualization	Connectivity USB 2.0, SDI/SDIO, Ethernet, LED illumination, Speaker	Micro SD Connector or eMMC Speaker Conn LED Out Conn



Give your vision the edge

- Application-based turnkey embedded vision solutions
- Edge AI for powerful on-device decision-making
- Flexible Cloud platform and end-to-end security

HARDWARE SPECIFICATIONS - iVS-CV22

Ambarella CV22 Based Vision SoC

	•	Quad-core Arm® Cortex®-A53 up to 1 GHz
Processor	•	NEON™ SIMD and FPU acceleration

• 10 nm low-power CMOS

• MIPI CSI-2, sLVDS, SLVS · 2 sensor inputs Sensor I/O

· Supports up to 20MP CMOS image sensor

· Up to 720 Mpixel/s maximum pixel rate

· Lens shading correction

Multi-exposure HDR

· 3D motion compensated noise reduction (MCTF)

Advanced **Image Signal** Processing

Audio

• Digital PTZ and Virtual Cameras

OSD engine, overlays, privacy mask

· Crop, mirror, flip, rotation

On-chip stitchingGeometric lens distortion correction

· Gamma compensation and color enhancement

· WDR with local tone mapping

 H.265 / HEVC, H.264, MJPEG Up to 4KP60 encoding performance Video **Processing** · Up to 8 simultaneous stream encodes · Dynamic region of interest (ROI)

Multiple CBR and VBR rate control modules

 CVFlow® vision processor for CNN / DNN edge analytics
 Pre-integrated AI Detectors or provide your own AI Power Intelligence · Can utilize models trained with industry-standard tools Video Analytics

such as Caffe, TensorFlow or PyTorch

• Wi-Fi 802.11a/b/g/n/ac (integrated) Networking · mini-PCIe LTE Module (optional) & Connectivity

Audio Codec

• 10/100/1000Mbps Ethernet PoE Module (optional)

 Line In and Line Out · 16Gb LPDDR4 DRAM

 4Gb NAND Flash Memory · Optional eMMC storage

USB 2.0 (Device / Host)

Micro SD

· SPI, I2C, JTAG, UART, GPIO, PWM, ADC **Interfaces**

• LED Flash Control

• Expansion I/O Port: MIPI-DSI, HDMI, GPIO

 AES / SHA1 / SHA2-256 crypto acceleration
 Secure boot with TrustZone® and secure memory, TRNG, Security

OTP, DRAM scrambling and virtualization

 12 VDC +/- 15% Power In

• Board size - 89 x 89 (mm) / 3.5 x 3.5 (inch) **Physical**

· Custom board size available

 Operating temperature: -20°C to 50°C **Environmental**

Operating humidity: 5% to 90%

os

Camera Modules

Sensor modules up to 20MP

Multiple lens options

• IR or white LED illumination options

• IR Filter for night vision options



SECURITY / **ACCESS CONTROL**



PRECISION FARMING



DRONES



INDUSTRIAL / **ROBOTICS**



IoT



AFTERMARKET AUTOMOTIVE



Additional information:


For compatible image sensor modules (iSM's) contact us at vision@ienso.com













Established in 2003, iENSO provides embedded vision data systems that help global brands turn their products into vision data devices. iENSO provides fully secure end-to-end solutions that capture vision data and process it at the Edge and in the Cloud, giving product companies the ability to unlock the benefits of recurring revenue and data monetization.

Americas

Global HQ Toronto 20 Mural St. Richmond Hill, ON Canada L4B 1K3 (905) 763-6938 • vision@ienso.com

Kyiv, Ukraine • EU@ienso.com

Middle East

Tel Aviv, Israel • ME@ienso.com

Taipei, Taiwan • Asia@ienso.com